



### Content

100% Polyurethane

### Backing

100% Polyester

### Finish



### Characteristics

No Heavy Metals  
Formaldehyde Free  
Polycarbonate Resin System

### Performance

Superior Abrasion  
CFFA 1-a, ASTM D-4157  
400,000 cycles, Wyzenbeek Wire Screen

Cold Crack -10°F  
CFFA 6-a

UV Stabilized Pigments  
QUV: ASTM D-4329 / CFFA-2 c2  
40 hours

Hydrolytic Stability  
5 Year Hydrolysis



This fabric meets or exceeds these ACT performance guidelines.  
\*Certification Marks owned by ACT\*

### Flame Retardancy\*

California T.B. 117 - 2013  
FMVSS 302  
IMO FTP 2010  
Code MSC.307(88), Part 8, 3.1 & 3.2  
NFPA 260 - Class I  
UFAC - Class I  
ASTM E84 Adehered - Class I  
BS 5852 - Source #0  
EN 1021 - Part 1 and 2

\*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

### Specifics

Weight: 15 oz.  
Width: 54 in.  
Roll Size: 30 yd.

### Applications

Corporate  
Restaurant  
Hospitality  
Sunroom  
Marine Interiors  
Auto | RV  
Residential Interiors